NSN 5945-00-272-5536

Electromagnetic Relay - Page 1 of 2

Unc single mounting facility



View Online at https://aerobasegroup.com/nsn/5945-00-272-5536

The state of the s
Thread Class:
2a single mounting facility
Overall Length:
3.810 inches
Overall Height:
2.000 inches
Overall Width:
1.750 inches
Environmental Protection:
Vibration proof
Winding Quantity:
2
Coil Quantity:
1
Winding Dc Resistance Rating:
10.0 ohms first winding
Duty Type:
Continuous
Mounting Facility Type And Quantity:
3 threaded stud single mounting facility
Pile-up Main Contact Form Arrangement:
2a2b
Features Provided:
Polarized and latching contacts
Thready Qty Per Inch (tpi):
32 single mounting facility
32 single mounting facility Thread Size:
Thread Size:
Thread Size: 0.164 inches single mounting facility
Thread Size: 0.164 inches single mounting facility Mounting Facility Pattern:
Thread Size: 0.164 inches single mounting facility Mounting Facility Pattern: Triangle single mounting facility
Thread Size: 0.164 inches single mounting facility Mounting Facility Pattern: Triangle single mounting facility Operating Current Rating And Type:
Thread Size: 0.164 inches single mounting facility Mounting Facility Pattern: Triangle single mounting facility Operating Current Rating And Type: 15.0 milliamperes dc all windings
Thread Size: 0.164 inches single mounting facility Mounting Facility Pattern: Triangle single mounting facility Operating Current Rating And Type: 15.0 milliamperes dc all windings Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:
Thread Size: 0.164 inches single mounting facility Mounting Facility Pattern: Triangle single mounting facility Operating Current Rating And Type: 15.0 milliamperes dc all windings Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle: 2.594 inches single mounting facility
Thread Size: 0.164 inches single mounting facility Mounting Facility Pattern: Triangle single mounting facility Operating Current Rating And Type: 15.0 milliamperes dc all windings Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle: 2.594 inches single mounting facility Operating Voltage Rating And Type At Specificationified Temp:
Thread Size: 0.164 inches single mounting facility Mounting Facility Pattern: Triangle single mounting facility Operating Current Rating And Type: 15.0 milliamperes dc all windings Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle: 2.594 inches single mounting facility Operating Voltage Rating And Type At Specificationified Temp: 18.0 volts dc 25 degrees celsius all windings
Thread Size: 0.164 inches single mounting facility Mounting Facility Pattern: Triangle single mounting facility Operating Current Rating And Type: 15.0 milliamperes dc all windings Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle: 2.594 inches single mounting facility Operating Voltage Rating And Type At Specificationified Temp: 18.0 volts dc 25 degrees celsius all windings Main Contact Load Current Rating At Maximum Rated Voltage:
Thread Size: 0.164 inches single mounting facility Mounting Facility Pattern: Triangle single mounting facility Operating Current Rating And Type: 15.0 milliamperes dc all windings Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle: 2.594 inches single mounting facility Operating Voltage Rating And Type At Specificationified Temp: 18.0 volts dc 25 degrees celsius all windings Main Contact Load Current Rating At Maximum Rated Voltage: 3.0 amperes ac resistive load

NSN 5945-00-272-5536

Electromagnetic Relay - Page 2 of 2



Terminal Type Ar	nd Quantity:
------------------	--------------

12 pin all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300