NSN 5945-00-283-4894

Electromagnetic Relay - Page 1 of 2

N/a



View Online at https://aerobasegroup.com/nsn/5945-00-283-4894

| Thread Class |
|--|
| Thread Class: |
| 2a single mounting facility Overall Length: |
| 7.500 inches |
| Overall Height: |
| 4.250 inches |
| Overall Width: |
| 3.875 inches |
| Frequency In Hertz: |
| 60.0 |
| Winding Quantity: |
| 1 |
| Coil Quantity: |
| 1 |
| Winding Dc Resistance Rating: |
| 175.0 ohms single winding |
| Duty Type: |
| Continuous |
| Mounting Facility Type And Quantity: |
| 3 threaded stud single mounting facility |
| Thread Size: |
| 0.190 inches single mounting facility |
| Mounting Facility Pattern: |
| Triangle single mounting facility |
| Nonpile-up Main Contact Arrangement: |
| 1 pole, double throw, one position momentary |
| Time Delay: |
| 0.20 seconds adjustable operate time and 3.00 minutes adjustable operate time |
| Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle: |
| 6.438 inches single mounting facility |
| Operating Voltage Rating And Type At Specificationified Temp: |
| 230.0 volts ac 25 degrees celsius single winding |
| Main Contact Load Current Rating At Maximum Rated Voltage: |
| 5.0 amperes ac resistive load |
| Main Contact Maximum Voltage Rating In Volts: |
| 250.0 ac |
| Thread Series Designator: |
| Unc single mounting facility |
| Terminal Type And Quantity: |
| 5 pin all functions |
| Shelf Life: |

NSN 5945-00-283-4894

Electromagnetic Relay - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300