

View Online at <https://aerobasegroup.com/nsn/5945-00-283-6538>

Overall Length:

3.000 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.250 inches first mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.625 inches second mounting facility

Overall Height:

3.218 inches

Overall Width:

2.666 inches

Case Material:

Metal

Unthreaded Mounting Hole Diameter:

0.173 inches second mounting facility

Fragility Factor:

Moderately rugged

Winding Quantity:

1

Purpose For Which Designed:

General

Coil Quantity:

1

Duty Type:

Continuous

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

6 unthreaded hole second mounting facility

Storage Type:

General purpose warehouse

Cubic Measure:

25.737 cubic inches

Mounting Facility Pattern:

Rectangular second mounting facility

Nonpile-up Main Contact Arrangement:

1 pole, single throw, normally open, double make, momentary action

Operating Current Rating And Type:

25.0 amperes dc single winding

Operating Voltage Rating And Type At Specificationified Temp:

28.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

20.0 amperes dc inductive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Test Data Document:

81349-mil-r-6106 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

4 screw all functions

Specification Data:

96906-ms25035 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300

Mil-std (military Standard):

Mil-r-6106 spec.