## NSN 5945-00-284-3155

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-284-3155

**Thread Class:** 

2b single mounting facility

**Overall Length:** 

1.620 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.313 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.500 inches single mounting facility

**Overall Height:** 

1.870 inches

Overall Width:

1.530 inches

**Environmental Protection:** 

Fungus proof

**End Application:** 

Type no. An/frr-3 and 3d

**Winding Quantity:** 

1

**Coil Quantity:** 

ı

Winding Dc Resistance Rating:

1.024 kilohms single winding

**Duty Type:** 

Continuous

**Mounting Facility Type And Quantity:** 

4 clinch nut single mounting facility

Thready Qty Per Inch (tpi):

32 single mounting facility

**Thread Size:** 

0.138 inches single mounting facility

**Mounting Facility Pattern:** 

Rectangular single mounting facility

**Operating Current Rating And Type:** 

49.0 milliamperes dc single winding

**Operating Voltage Rating And Type At Specificationified Temp:** 

50.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

15.0 amperes ac resistive load and 15.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

110.0 ac and 24.0 dc

**Special Features:** 

A. Fungus proof on coil and phenolic parts

## NSN 5945-00-284-3155

Electromagnetic Relay - Page 2 of 2



T	'nr	ead	<b>Series</b>	Desig	nator
-			-0	-00.9	

Unc single mounting facility

**Terminal Type And Quantity:** 

8 pin all functions

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A03300