NSN 5945-00-295-3189

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-295-3189

Overall Length: 3.250 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 2.850 inches single mounting facility Overall Height: 1.620 inches Overall Width: 1.250 inches Environmental Protection: Salt spray resistant Unthreaded Mounting Hole Diameter: 0.144 inches single mounting facility Frequency In Hertz: 60.0 Winding Quantity:
Center To Center Distance Between Mounting Facilities Parallel To Length: 2.850 inches single mounting facility Overall Height: 1.620 inches Overall Width: 1.250 inches Environmental Protection: Salt spray resistant Unthreaded Mounting Hole Diameter: 0.144 inches single mounting facility Frequency In Hertz: 60.0
2.850 inches single mounting facility Overall Height: 1.620 inches Overall Width: 1.250 inches Environmental Protection: Salt spray resistant Unthreaded Mounting Hole Diameter: 0.144 inches single mounting facility Frequency In Hertz: 60.0
Overall Height: 1.620 inches Overall Width: 1.250 inches Environmental Protection: Salt spray resistant Unthreaded Mounting Hole Diameter: 0.144 inches single mounting facility Frequency In Hertz: 60.0
1.620 inches Overall Width: 1.250 inches Environmental Protection: Salt spray resistant Unthreaded Mounting Hole Diameter: 0.144 inches single mounting facility Frequency In Hertz: 60.0
Overall Width: 1.250 inches Environmental Protection: Salt spray resistant Unthreaded Mounting Hole Diameter: 0.144 inches single mounting facility Frequency In Hertz: 60.0
1.250 inches Environmental Protection: Salt spray resistant Unthreaded Mounting Hole Diameter: 0.144 inches single mounting facility Frequency In Hertz: 60.0
Environmental Protection: Salt spray resistant Unthreaded Mounting Hole Diameter: 0.144 inches single mounting facility Frequency In Hertz: 60.0
Salt spray resistant Unthreaded Mounting Hole Diameter: 0.144 inches single mounting facility Frequency In Hertz: 60.0
Unthreaded Mounting Hole Diameter: 0.144 inches single mounting facility Frequency In Hertz: 60.0
0.144 inches single mounting facility Frequency In Hertz: 60.0
Frequency In Hertz: 60.0
60.0
Winding Quantity:
2
Coil Quantity:
2
Winding Dc Resistance Rating:
600.0 ohms all windings
Duty Type:
Continuous
Mounting Facility Type And Quantity:
2 unthreaded hole single mounting facility
Pile-up Main Contact Form Arrangement:
1a and 2a
Mounting Facility Pattern:
In-line single mounting facility
Operating Voltage Rating And Type At Specificationified Temp:
115.0 volts ac 25 degrees celsius all windings
Main Contact Load Current Rating At Maximum Rated Voltage:
1.5 amperes ac resistive load and 1.5 amperes dc resistive load
Main Contact Maximum Voltage Rating In Volts:
115.0 ac and 24.0 dc
Special Features:
A. Resistant to salt water spray
Terminal Type And Quantity:
10 pin all functions
Shelf Life:
N/a
Unit Of Measure:

--

NSN 5945-00-295-3189

Electromagnetic Relay - Page 2 of 2



Demilitarization:

No

Fiig:

A03300