NSN 5945-00-295-4306

Electromagnetic Relay - Page 1 of 2

12 pin all functions



View Online at https://aerobasegroup.com/nsn/5945-00-295-4306

| Thread Class: |
|--|
| 2a single mounting facility |
| Overall Length: |
| 3.810 inches |
| Overall Height: |
| 2.500 inches |
| Overall Width: |
| 1.750 inches |
| Environmental Protection: |
| Hermetic |
| End Application: |
| Type an/spq-5 |
| Winding Quantity: |
| 2 |
| Coil Quantity: |
| 1 |
| Winding Dc Resistance Rating: |
| 11.0 kilohms second winding |
| Duty Type: |
| Continuous |
| Mounting Facility Type And Quantity: |
| 3 threaded stud single mounting facility |
| Features Provided: |
| Polarized |
| Thread Size: |
| 0.164 inches single mounting facility |
| Mounting Facility Pattern: |
| Triangle single mounting facility |
| Nonpile-up Main Contact Arrangement: |
| 2 two circuit, both positions maintained |
| Operating Current Rating And Type: |
| 2.2 milliamperes dc all windings |
| Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle: |
| 2.593 inches single mounting facility |
| Main Contact Load Current Rating At Maximum Rated Voltage: |
| 5.00 amperes dc inductive load and 5.00 amperes ac inductive load |
| Main Contact Maximum Voltage Rating In Volts: |
| 24.0 dc and 115.0 ac |
| Thread Series Designator: |
| Unc single mounting facility |
| Terminal Type And Quantity: |

NSN 5945-00-295-4306

Electromagnetic Relay - Page 2 of 2



| _ | | | | | |
|---|---|------------|---|----|----|
| • | n | 0 1 | • | 12 | e: |
| | | | | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300