

View Online at <https://aerobasegroup.com/nsn/5945-00-295-6766>

Overall Length:

4.750 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.000 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.500 inches single mounting facility

Overall Height:

4.656 inches

Overall Width:

4.250 inches

Environmental Protection:

Splash proof

Unthreaded Mounting Hole Diameter:

0.196 inches single mounting facility

Winding Quantity:

2

Coil Quantity:

2

Winding Dc Resistance Rating:

7.7 ohms second winding

Duty Type:

Continuous

Arc Quenching Method:

Capacitor

Mounting Facility Type And Quantity:

4 unthreaded hole single mounting facility

Mounting Facility Pattern:

Rectangular single mounting facility

Operating Current Rating And Type:

5.2 amperes dc first winding

Operating Voltage Rating And Type At Specificationified Temp:

30.0 volts dc 25 degrees celsius all windings

Main Contact Load Current Rating At Maximum Rated Voltage:

3.9 amperes dc resistive load and 2.0 amperes dc resistive load and 4.0 amperes dc resistive load and 0.25 amperes dc resistive load and 15.0 amperes dc resistive load and 50.0 amperes dc resistive load and 5.2 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

175.0 dc and 10.0 dc and 175.0 dc and 40.0 dc and 30.0 dc and 175.0 dc and 30.0 dc

Special Features:

Current rating at maximum rated voltage amps 2.0, 4.0, 0.25, 15.0, 50.0, 5.2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A03300