NSN 5945-00-296-1700

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-296-1700

Overall Length:

10.891 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

9.562 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

7.125 inches single mounting facility

Overall Height:

6.187 inches

Overall Width:

8.453 inches

Environmental Protection:

Shock resistant

Unthreaded Mounting Hole Diameter:

0.406 inches single mounting facility

Frequency In Hertz:

60.0

Winding Quantity:

Coil Quantity:

.

Winding Dc Resistance Rating:

2.8 ohms single winding

Duty Type:

Continuous

Mounting Facility Type And Quantity:

4 unthreaded hole single mounting facility

Mounting Facility Pattern:

Rectangular single mounting facility

Nonpile-up Main Contact Arrangement:

3 pole, single throw, normally open, momentary action

Time Delay:

0.0250 seconds fixed operate time

Nonpile-up Auxiliary Contact Arrangement:

2 pole, single throw, normally open, momentary action

Auxiliary Contact Maximum Voltage Rating In Volts:

440.0 ac

Operating Voltage Rating And Type At Specificationified Temp:

115.0 volts ac 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

135.0 amperes ac resistive load

Main Contact Maximum Voltage Rating In Volts:

440.0 ac

NSN 5945-00-296-1700

Electromagnetic Relay - Page 2 of 2



Auxiliary	/ Contact	Load (Current	Rating	Αt	Maximum	Rated	Voltage:

5.0 amperes ac resistive load

Terminal Type And Quantity:

12 screw all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300