NSN 5945-00-296-1707

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.co m/nen/50/5-00-206-1707

View Online at https://aerobasegroup.com/nsn/5945-00-296-1707
Overall Length:
6.135 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
5.125 inches single mounting facility
Center To Center Distance Between Mounting Facilities Parallel To Width:
4.625 inches single mounting facility
Overall Height:
14.827 inches
Overall Width:
5.375 inches
Case Material:
Plastic
Unthreaded Mounting Hole Diameter:
0.281 inches single mounting facility
Fragility Factor:
Moderately rugged
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Winding Dc Resistance Rating:
355.0 ohms single winding
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
4 unthreaded hole single mounting facility
Storage Type:
General purpose warehouse
Cubic Measure:
488.930 cubic inches
Mounting Facility Pattern:
Rectangular single mounting facility
Nonpile-up Main Contact Arrangement:
1 pole, single throw, normally closed, momentary action

1.3 amperes dc single winding

Operating Current Rating And Type:

Time Delay:

0.055 seconds fixed operate time

NSN 5945-00-296-1707

Electromagnetic Relay - Page 2 of 2



Nonpile-up Auxiliary Contact Arrangement:

2 pole, double throw, one position momentary

Auxiliary Contact Maximum Voltage Rating In Volts:

230.0 ac

Operating Voltage Rating And Type At Specificationified Temp:

48.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

200.0 amperes ac resistive load

Main Contact Maximum Voltage Rating In Volts:

30000.0 ac

Auxiliary Contact Load Current Rating At Maximum Rated Voltage:

15.0 amperes ac resistive load

Terminal Type And Quantity:

10 screw all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300