# NSN 5945-00-321-8215

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-321-8215

# **Thread Class:**

2a single mounting facility

# **Overall Length:**

2.249 inches

# Center To Center Distance Between Mounting Facilities Parallel To Length:

1.187 inches single mounting facility

# Center To Center Distance Between Mounting Facilities Parallel To Width:

0.687 inches single mounting facility

# **Overall Height:**

1.032 inches

# **Overall Width:**

1.531 inches

**Environmental Protection:** 

#### Dustproof

# Winding Quantity:

# **Coil Quantity:**

2

2

#### Winding Dc Resistance Rating:

200.0 ohms first winding

**Duty Type:** 

Continuous

#### Mounting Facility Type And Quantity:

4 threaded stud single mounting facility

#### **Features Provided:**

Polarized and latching contacts

#### Thready Qty Per Inch (tpi):

32 single mounting facility

#### Thread Size:

0.138 inches single mounting facility

#### **Mounting Facility Pattern:**

Rectangular single mounting facility

#### **Nonpile-up Main Contact Arrangement:**

2 pole, double throw, one position momentary

#### **Operating Current Rating And Type:**

2.0 amperes dc all windings

#### **Time Delay:**

0.025 seconds fixed operate time

#### **Operating Voltage Rating And Type At Specificationified Temp:**

26.5 volts dc 25 degrees celsius all windings

# Main Contact Load Current Rating At Maximum Rated Voltage:

10.0 amperes ac resistive load and 10.0 amperes dc resistive load

NSN 5945-00-321-8215

Electromagnetic Relay - Page 2 of 2



Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Thread Series Designator:

Unc single mounting facility

Terminal Type And Quantity:

10 pin all functions

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A03300