## NSN 5945-00-324-2982

Reed Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-324-2982

**Thread Class:** 2a single mounting facility **Overall Length:** 1.500 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 1.200 inches single mounting facility **Overall Height:** 0.720 inches **Overall Width:** 0.830 inches **Environmental Protection:** Dustproof Winding Quantity: **Coil Quantity:** Winding Dc Resistance Rating: 1.7 kilohms single winding **Duty Type:** Continuous **Mounting Facility Type And Quantity:** 2 threaded stud single mounting facility Thready Qty Per Inch (tpi): 40 single mounting facility **Thread Size:** 0.112 inches single mounting facility **Mounting Facility Pattern:** Two position in-line single mounting facility **Nonpile-up Main Contact Arrangement:** 1 pole, single throw, normally open, momentary action **Operating Current Rating And Type:** 6.0 milliamperes dc single winding **Operating Voltage Rating And Type At Specificationified Temp:** 10.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 100.0 milliamperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 100.0 dc **Thread Series Designator:** 

Unc single mounting facility

**Terminal Type And Quantity:** 

4 pin all functions

## NSN 5945-00-324-2982

Reed Relay - Page 2 of 2



	<b>L</b> -	16		ife	_
3	ne	п	_	пе	Ξ

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A03300