NSN 5945-00-329-7104

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-329-7104

view Offilitie at https://defobasegroup.com/nsi//0545-00-025-7104
Overall Length:
4.520 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.750 inches single mounting facility
Center To Center Distance Between Mounting Facilities Parallel To Width:
2.880 inches single mounting facility
Overall Height:
3.090 inches
Overall Width:
3.250 inches
Case Material:
Metal
Environmental Protection:
Dustproof
Unthreaded Mounting Hole Diameter:
0.199 inches single mounting facility
Fragility Factor:
Moderately rugged
Frequency In Hertz:
60.0
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
6 unthreaded hole single mounting facility
Storage Type:
General purpose warehouse
Cubic Measure:
45.392 cubic inches
Mounting Facility Pattern:
Rectangular single mounting facility
Nonpile-up Main Contact Arrangement:
2 pole, double throw, one position momentary
Time Delay:

Time Delay.

 $3.00 \; \text{minutes} \; \; \text{adjustable operate time} \; \; \text{and} \; \; 30.00 \; \text{minutes} \; \; \text{adjustable operate time}$

NSN 5945-00-329-7104

Electromagnetic Relay - Page 2 of 2



Operating Voltage Rating And Type At Specificationified Temp:

120.0 volts ac 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

10.0 amperes ac resistive load and 500.0 milliamperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

480.0 ac and 110.0 dc

Terminal Type And Quantity:

8 screw all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300