## NSN 5945-00-333-1011

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-333-1011

**Thread Class:** 2b single mounting facility **Overall Length:** 4.000 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 0.750 inches single mounting facility **Overall Height:** 1.210 inches **Overall Width:** 2.060 inches Winding Quantity: **Coil Quantity:** Winding Dc Resistance Rating: 400.0 ohms all windings **Duty Type:** Continuous **Mounting Facility Type And Quantity:** 2 threaded stud single mounting facility **Pile-up Main Contact Form Arrangement:** 1a2c2b **Thread Size:** 0.164 inches single mounting facility **Mounting Facility Pattern:** In-line single mounting facility **Operating Current Rating And Type:** 28.8 milliamperes dc single winding Operating Voltage Rating And Type At Specificationified Temp: 48.0 volts dc 25 degrees celsius all windings Main Contact Load Current Rating At Maximum Rated Voltage: 3.00 amperes dc resistive load **Main Contact Maximum Voltage Rating In Volts:** 50.0 dc **Thread Series Designator:** Unc single mounting facility **Terminal Type And Quantity:** 16 pin all functions Fsc Application Data (non-core): Panel telephone switchboard

Shelf Life:

N/a

## NSN 5945-00-333-1011

Electromagnetic Relay - Page 2 of 2



|  |  | eas |  |
|--|--|-----|--|

--

Demilitarization:

No

Fiig:

A03300