NSN 5945-00-333-3572

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-333-3572

| view Online at https://aerobasegroup.com/hsh/5945-00-333-3572 |
|---|
| Thread Class: |
| 2b single mounting facility |
| Overall Length: |
| 1.437 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.312 inches single mounting facility |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 0.500 inches single mounting facility |
| Overall Height: |
| 1.750 inches |
| Overall Width: |
| 1.375 inches |
| Environmental Protection: |
| Dustproof |
| Winding Quantity: |
| 1 |
| Coil Quantity: |
| 1 |
| Duty Type: |
| Continuous |
| Mounting Facility Type And Quantity: |
| 4 threaded hole single mounting facility |
| Thready Qty Per Inch (tpi): |
| 40 single mounting facility |
| Thread Size: |
| 0.125 inches single mounting facility |
| Mounting Facility Pattern: |
| Rectangular single mounting facility |
| Nonpile-up Main Contact Arrangement: |
| 1 pole, single throw, normally open, momentary action |
| Operating Voltage Rating And Type At Specificationified Temp: |
| 28.0 volts dc 25 degrees celsius single winding |
| Main Contact Load Current Rating At Maximum Rated Voltage: |
| 1.0 amperes ac resistive load and 1.0 amperes dc resistive load |
| Main Contact Maximum Voltage Rating In Volts: |
| 115.0 ac and 28.0 dc |
| Thread Series Designator: |
| Unc single mounting facility |
| Terminal Type And Quantity: |
| 4 tab, solder lug all functions |
| Shelf Life: |

N/a

NSN 5945-00-333-3572

Electromagnetic Relay - Page 2 of 2



| | 1 | :. | ~ | 84 | | | | |
|---|----|----|----|-----|----|----|------|---|
| ι | JN | IT | UΤ | IVI | ea | Sι | ire: | • |

--

Demilitarization:

No

Fiig:

A03300