## NSN 5945-00-340-1609

Electromagnetic Relay - Page 1 of 2



## View Online at https://aerobasegroup.com/nsn/5945-00-340-1609 **Overall Length:** 1.180 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 1.000 inches single mounting facility **Overall Height:** 0.612 inches Overall Width: 0.410 inches **Environmental Protection:** Shock resistant and vibration resistant **Unthreaded Mounting Hole Diameter:** 0.091 inches single mounting facility and 0.101 inches single mounting facility Winding Quantity: **Coil Quantity:** Winding Dc Resistance Rating: 38.0 ohms single winding **Duty Type:** Continuous **Mounting Facility Type And Quantity:** 2 unthreaded hole single mounting facility **Features Provided:** Polarized **Mounting Facility Pattern:** In-line single mounting facility **Nonpile-up Main Contact Arrangement:** 2 pole, double throw, one position momentary Operating Voltage Rating And Type At Specificationified Temp: 6.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 100.0 milliamperes dc resistive load **Main Contact Maximum Voltage Rating In Volts:** 8.0 dc **Precious Material And Location:** Terminal surfaces gold **Precious Material:** Gold **Terminal Type And Quantity:** 8 pin all functions

N/a

Shelf Life:

## NSN 5945-00-340-1609

Electromagnetic Relay - Page 2 of 2



**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A03300