NSN 5945-00-343-3722

Electrical Solenoid - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-343-3722

| Body Style: |
|--|
| Open frame |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.312 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 1.812 inches |
| Body Length: |
| 2.062 inches |
| Body Width: |
| 1.562 inches |
| Body Height: |
| 1.156 inches |
| Case Material: |
| Metal |
| Case Surface Treatment: |
| Any acceptable |
| Environmental Protection: |
| Humidity proof |
| Unthreaded Mounting Hole Diameter: |
| 0.161 inches |
| Inclosure Type: |
| Partially enclosed, shell |
| Magnetic Coil Quantity: |
| 1 |
| Electrical Resistance: |
| 250.00 ohms |
| Duty Type: |
| Continuous |
| Terminal Location: |
| Circumference |
| Voltage Rating In Volts: |
| 27.5 dc |
| Mounting Facility Type And Quantity: |
| 4 unthreaded hole |
| Current Rating: |
| 3.66 amperes |
| Torque Rating And Type: |
| 8.00 inch-pounds starting and 16.00 inch-pounds end |
| Actuator Stroke Type: |
| Rotary |
| Power Takeoff Connection Type: |
| Plain-drilled |
| 8.00 inch-pounds starting and 16.00 inch-pounds end Actuator Stroke Type: Rotary Power Takeoff Connection Type: |
| |

NSN 5945-00-343-3722

Electrical Solenoid - Page 2 of 2



Mounting Facility Pattern:

Four position rectangular

Rotation Direction And Energizing Stroke In Angular Deg:

30.0 counterclockwise

Special Features:

Equipped with a lever and taper pin

Terminal Type And Quantity:

2 wire lead

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A134a0