NSN 5945-00-346-1703

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-346-1703

Thread Class:

2b single mounting facility

Overall Length:

2.250 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.312 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.500 inches single mounting facility

Overall Height:

1.870 inches

Overall Width:

1.620 inches

End Application:

Type no. lp-354/tps-1d

Winding Quantity:

1

Coil Quantity:

Winding Dc Resistance Rating:

5.0 kilohms single winding

Duty Type:

Continuous

Mounting Facility Type And Quantity:

4 threaded hole single mounting facility

Thread Size:

0.138 inches single mounting facility

Mounting Facility Pattern:

Rectangular single mounting facility

Nonpile-up Main Contact Arrangement:

3 pole, double throw, one position momentary

Operating Current Rating And Type:

23.0 milliamperes dc single winding

Operating Voltage Rating And Type At Specificationified Temp:

115.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

10.0 amperes ac resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac

Thread Series Designator:

Unc single mounting facility

Terminal Type And Quantity:

2 tab, solder lug energizing element

NSN 5945-00-346-1703

Electromagnetic Relay - Page 2 of 2



	Fsc /	٩p	plication	Data ((non-core)):
--	-------	----	-----------	--------	------------	----

Relay armature, except engine

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300