## NSN 5945-00-394-1695

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-394-1695

Thread Class:
2a first mounting facility
Thread Direction:
Right-hand first mounting facility
Thread Length:
0.171 inches first mounting facility
Overall Length:
0.938 inches
Overall Height:
1.187 inches
Overall Width:
0.748 inches
Environmental Protection:
Dustproof
Fragility Factor:
Moderately rugged
Contact Material:
Silver
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Winding Dc Resistance Rating:
52.0 ohms single winding
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
2 threaded stud first mounting facility
Storage Type:
General purpose warehouse
Cubic Measure:
0.832 cubic inches
Thready Qty Per Inch (tpi):
48 first mounting facility
Thread Size:
0.099 inches first mounting facility
Mounting Facility Pattern:
In-line first mounting facility

## NSN 5945-00-394-1695

Electromagnetic Relay - Page 2 of 2



## **Nonpile-up Main Contact Arrangement:**

2 pole, double throw, one position momentary

**Operating Voltage Rating And Type At Specificationified Temp:** 

12.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

3.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 dc

**Precious Material And Location:** 

Contacts silver

**Precious Material:** 

Silver

**Thread Series Designator:** 

Unc first mounting facility

**Terminal Type And Quantity:** 

10 tab, solder lug all functions

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A03300