NSN 5945-00-401-6223

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-401-6223

Thread Class: 2a single mounting facility **Overall Length:** 1.094 inches **Overall Height:** 1.313 inches **Overall Width:** 0.625 inches **Environmental Protection:** Dustproof Winding Quantity: **Coil Quantity:** Winding Dc Resistance Rating: 700.0 ohms single winding **Duty Type:** Continuous **Mounting Facility Type And Quantity:** 1 threaded stud single mounting facility Thready Qty Per Inch (tpi): 80 single mounting facility **Thread Size:** 0.060 inches single mounting facility **Nonpile-up Main Contact Arrangement:** 4 pole, double throw, one position momentary **Operating Current Rating And Type:** 34.0 milliamperes dc single winding Time Delay: 0.014 seconds fixed operate time Operating Voltage Rating And Type At Specificationified Temp: 24.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 1.0 amperes dc resistive load **Main Contact Maximum Voltage Rating In Volts:** 24.0 dc **Energizing Element Power Rating:** 1.0 watts **Special Features:** A. Rubber spacer glued on top

Thread Series Designator: Unef single mounting facility

NSN 5945-00-401-6223

Electromagnetic Relay - Page 2 of 2



| Terminal T | ype And | Quantity: |
|------------|---------|-----------|
|------------|---------|-----------|

14 tab, solder lug all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300