NSN 5945-00-402-3903

Electromagnetic Relay - Page 1 of 2

0.850 inches single mounting facility

Environmental Protection:

Unthreaded Mounting Hole Diameter: 0.096 inches single mounting facility

Overall Length: 1.062 inches

Overall Height: 0.320 inches Overall Width: 0.470 inches Case Material:

Metal

Hermetic

Fragility Factor:

Moderately rugged



View Online at https://aerobasegroup.com/nsn/5945-00-402-3903

Center To Center Distance Between Mounting Facilities Parallel To Length:

Winding Quantity:
1
Coil Quantity:
1
Winding Dc Resistance Rating:
210.0 ohms single winding
Duty Type:
Continuous
Mounting Facility Type And Quantity:
2 unthreaded hole single mounting facility
Storage Type:
General purpose warehouse
Cubic Measure:
0.160 cubic inches
Mounting Facility Pattern:
In-line single mounting facility
Nonpile-up Main Contact Arrangement:
2 pole, double throw, one position momentary
Time Delay:
0.004 seconds fixed operate and release time
Operating Voltage Rating And Type At Specificationified Temp:
12.0 volts dc 25 degrees celsius single winding
Main Contact Load Current Rating At Maximum Rated Voltage:
125.0 milliamperes ac resistive load and 2.0 milliamperes dc resistive load
Main Contact Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc

NSN 5945-00-402-3903

Electromagnetic Relay - Page 2 of 2



Test Data Document:

81349-mil-r-5757 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

8 wire hook all functions

Specification Data:

81349-mil-r-5757/23 government specification

Specification Or Standard:

No. -5757/37-023 part

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A03300