# NSN 5945-00-402-7506

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-402-7506

### **Overall Length:**

Between 3.781 inches and 3.905 inches

### Center To Center Distance Between Mounting Facilities Parallel To Length:

3.120 inches first mounting facility and 3.130 inches first mounting facility

#### **Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.995 inches second mounting facility and 2.005 inches second mounting facility

### **Overall Height:**

3.375 inches

#### **Overall Width:**

3.375 inches

#### **Unthreaded Mounting Hole Diameter:**

0.203 inches first mounting facility

#### **Fragility Factor:**

Moderately rugged

#### Frequency In Hertz:

400.0

### **Winding Quantity:**

!

### **Purpose For Which Designed:**

General

### **Coil Quantity:**

1

### **Duty Type:**

Continuous

### **Mounting Facility Type And Quantity:**

2 unthreaded hole second mounting facility

### Storage Type:

General purpose warehouse

## Cubic Measure:

44.480 cubic inches

### **Mounting Facility Pattern:**

In-line second mounting facility

### Nonpile-up Main Contact Arrangement:

3 pole, single throw, normally open, momentary action

### Time Delay:

0.024 seconds fixed operate time

### Operating Voltage Rating And Type At Specificationified Temp:

120.0 volts ac 25 degrees celsius single winding

### Main Contact Load Current Rating At Maximum Rated Voltage:

40.0 amperes dc resistive load

#### Main Contact Maximum Voltage Rating In Volts:

600.0 dc

# NSN 5945-00-402-7506

Electromagnetic Relay - Page 2 of 2



T	erm	inal	Type	Δnd	Ou	antity	,.
ı	GIIII	ıııaı	IVDE	Allu	чu	annını	

8 screw all functions

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A03300