NSN 5945-00-403-2427

Electromagnetic Relay - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5945-00-403-2427

1.680 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 1.062 inches single mounting facility Overall Height: 0.440 inches Overall Width: 1.320 inches Environmental Protection: Hermetic Unthreaded Mounting Hole Diameter: 0.120 inches single mounting facility Winding Quantity: 1 Coil Quantity: 1 Duty Type: Continuous Mounting Facility Type And Quantity: 2 unthreaded hole single mounting facility Mounting Facility Pattern: In-line single mounting facility Nonpile-up Main Contact Arrangement: 2 pole, double throw, one position momentary Time Delay: 0.10 seconds fixed operate time Operating Voltage Rating And Type At Specificationified Temp: 24.5 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 2.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 30.0 dc Terminal Type And Quantity: 8 pin all functions Shelf Life: N/a Unit Of Measure: Demilitarization:	Overall Length:
1.062 inches single mounting facility Overall Height: 0.440 inches Overall Width: 1.320 inches Environmental Protection: Hermetic Unthreaded Mounting Hole Diameter: 0.120 inches single mounting facility Winding Quantity: 1 Coil Quantity: 1 Duty Type: Continuous Mounting Facility Type And Quantity: 2 unthreaded hole single mounting facility Mounting Facility Pattern: In-line single mounting facility Nonpile-up Main Contact Arrangement: 2 pole, double throw, one position momentary Time Delay: 0.10 seconds fixed operate time Operating Voltage Rating And Type At Specificationified Temp: 24.5 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 2.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 30.0 dc Terminal Type And Quantity: 8 pin all functions Shelf Life: N/a Unit Of Measure:	1.680 inches
Overall Height: 0.440 inches Overall Width: 1.320 inches Environmental Protection: Hermetic Unthreaded Mounting Hole Diameter: 0.120 inches single mounting facility Winding Quantity: 1 Coil Quantity: 1 Duty Type: Continuous Mounting Facility Type And Quantity: 2 unthreaded hole single mounting facility Mounting Facility Pattern: In-line single mounting facility Nonpile-up Main Contact Arrangement: 2 pole, double throw, one position momentary Time Delay: 0.10 seconds fixed operate time Operating Voltage Rating And Type At Specificationified Temp: 24.5 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 2.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 30.0 dc Terminal Type And Quantity: 8 pin all functions Shelf Life: N/a Unit Of Measure:	Center To Center Distance Between Mounting Facilities Parallel To Length:
0.440 inches Overall Width: 1.320 inches Environmental Protection: Hermetic Unthreaded Mounting Hole Diameter: 0.120 inches single mounting facility Winding Quantity: 1 Coil Quantity: 1 Duty Type: Continuous Mounting Facility Type And Quantity: 2 unthreaded hole single mounting facility Mounting Facility Pattern: In-line single mounting facility Nonpile-up Main Contact Arrangement: 2 pole, double throw, one position momentary Time Delay: 0.10 seconds fixed operate time Operating Voltage Rating And Type At Specificationified Temp: 24.5 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 2.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 30.0 dc Terminal Type And Quantity: 8 pin all functions Shelf Life: N/a Unit Of Measure:	1.062 inches single mounting facility
Overall Width: 1.320 inches Environmental Protection: Hermetic Unthreaded Mounting Hole Diameter: 0.120 inches single mounting facility Winding Quantity: 1 Coil Quantity: 1 Duty Type: Continuous Mounting Facility Type And Quantity: 2 unthreaded hole single mounting facility Mounting Facility Pattern: In-line single mounting facility Nonpile-up Main Contact Arrangement: 2 pole, double throw, one position momentary Time Delay: 0.10 seconds fixed operate time Operating Voltage Rating And Type At Specificationified Temp: 24.5 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 2.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 30.0 dc Terminal Type And Quantity: 8 pin all functions Shelf Life: N/a Unit Of Measure:	Overall Height:
1.320 inches Environmental Protection: Hermetic Unthreaded Mounting Hole Diameter: 0.120 inches single mounting facility Winding Quantity: 1 Coil Quantity: 1 Duty Type: Continuous Mounting Facility Type And Quantity: 2 unthreaded hole single mounting facility Mounting Facility Pattern: In-line single mounting facility Nonpile-up Main Contact Arrangement: 2 pole, double throw, one position momentary Time Delay: 0.10 seconds fixed operate time Operating Voltage Rating And Type At Specificationified Temp: 24.5 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 2.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 30.0 dc Terminal Type And Quantity: 8 pin all functions Shelf Life: N/a Unit Of Measure:	0.440 inches
Environmental Protection: Hermetic Unthreaded Mounting Hole Diameter: 0.120 inches single mounting facility Winding Quantity: 1 Coil Quantity: 1 Duty Type: Continuous Mounting Facility Type And Quantity: 2 unthreaded hole single mounting facility Mounting Facility Pattern: In-line single mounting facility Nonpile-up Main Contact Arrangement: 2 pole, double throw, one position momentary Time Delay: 0.10 seconds fixed operate time Operating Voltage Rating And Type At Specificationified Temp: 24.5 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 2.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 30.0 dc Terminal Type And Quantity: 8 pin all functions Shelf Life: N/a Unit Of Measure:	Overall Width:
Hermetic Unthreaded Mounting Hole Diameter: 0.120 inches single mounting facility Winding Quantity: 1 Coil Quantity: 1 Duty Type: Continuous Mounting Facility Type And Quantity: 2 unthreaded hole single mounting facility Mounting Facility Pattern: In-line single mounting facility Nonpile-up Main Contact Arrangement: 2 pole, double throw, one position momentary Time Delay: 0.10 seconds fixed operate time Operating Voltage Rating And Type At Specificationified Temp: 24.5 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 2.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 30.0 dc Terminal Type And Quantity: 8 pin all functions Shelf Life: N/a Unit Of Measure:	1.320 inches
Unthreaded Mounting Hole Diameter: 0.120 inches single mounting facility Winding Quantity: 1 Coil Quantity: 1 Duty Type: Continuous Mounting Facility Type And Quantity: 2 unthreaded hole single mounting facility Mounting Facility Pattern: In-line single mounting facility Nonpile-up Main Contact Arrangement: 2 pole, double throw, one position momentary Time Delay: 0.10 seconds fixed operate time Operating Voltage Rating And Type At Specificationified Temp: 24.5 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 2.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 30.0 dc Terminal Type And Quantity: 8 pin all functions Shelf Life: N/a Unit Of Measure:	Environmental Protection:
O.120 inches single mounting facility Winding Quantity: 1 Coil Quantity: 1 Duty Type: Continuous Mounting Facility Type And Quantity: 2 unthreaded hole single mounting facility Mounting Facility Pattern: In-line single mounting facility Nonpile-up Main Contact Arrangement: 2 pole, double throw, one position momentary Time Delay: 0.10 seconds fixed operate time Operating Voltage Rating And Type At Specificationified Temp: 24.5 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 2.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 30.0 dc Terminal Type And Quantity: 8 pin all functions Shelf Life: N/a Unit Of Measure:	Hermetic
Winding Quantity: 1 Coil Quantity: 1 Duty Type: Continuous Mounting Facility Type And Quantity: 2 unthreaded hole single mounting facility Mounting Facility Pattern: In-line single mounting facility Nonpile-up Main Contact Arrangement: 2 pole, double throw, one position momentary Time Delay: 0.10 seconds fixed operate time Operating Voltage Rating And Type At Specificationified Temp: 24.5 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 2.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 30.0 dc Terminal Type And Quantity: 8 pin all functions Shelf Life: N/a Unit Of Measure:	Unthreaded Mounting Hole Diameter:
Coil Quantity: 1 Duty Type: Continuous Mounting Facility Type And Quantity: 2 unthreaded hole single mounting facility Mounting Facility Pattern: In-line single mounting facility Nonpile-up Main Contact Arrangement: 2 pole, double throw, one position momentary Time Delay: 0.10 seconds fixed operate time Operating Voltage Rating And Type At Specificationified Temp: 24.5 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 2.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 30.0 dc Terminal Type And Quantity: 8 pin all functions Shelf Life: N/a Unit Of Measure:	0.120 inches single mounting facility
Coil Quantity: 1 Duty Type: Continuous Mounting Facility Type And Quantity: 2 unthreaded hole single mounting facility Mounting Facility Pattern: In-line single mounting facility Nonpile-up Main Contact Arrangement: 2 pole, double throw, one position momentary Time Delay: 0.10 seconds fixed operate time Operating Voltage Rating And Type At Specificationified Temp: 24.5 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 2.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 30.0 dc Terminal Type And Quantity: 8 pin all functions Shelf Life: N/a Unit Of Measure:	Winding Quantity:
Duty Type: Continuous Mounting Facility Type And Quantity: 2 unthreaded hole single mounting facility Mounting Facility Pattern: In-line single mounting facility Nonpile-up Main Contact Arrangement: 2 pole, double throw, one position momentary Time Delay: 0.10 seconds fixed operate time Operating Voltage Rating And Type At Specificationified Temp: 24.5 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 2.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 30.0 dc Terminal Type And Quantity: 8 pin all functions Shelf Life: N/a Unit Of Measure:	1
Duty Type: Continuous Mounting Facility Type And Quantity: 2 unthreaded hole single mounting facility Mounting Facility Pattern: In-line single mounting facility Nonpile-up Main Contact Arrangement: 2 pole, double throw, one position momentary Time Delay: 0.10 seconds fixed operate time Operating Voltage Rating And Type At Specificationified Temp: 24.5 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 2.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 30.0 dc Terminal Type And Quantity: 8 pin all functions Shelf Life: N/a Unit Of Measure:	Coil Quantity:
Continuous Mounting Facility Type And Quantity: 2 unthreaded hole single mounting facility Mounting Facility Pattern: In-line single mounting facility Nonpile-up Main Contact Arrangement: 2 pole, double throw, one position momentary Time Delay: 0.10 seconds fixed operate time Operating Voltage Rating And Type At Specificationified Temp: 24.5 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 2.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 30.0 dc Terminal Type And Quantity: 8 pin all functions Shelf Life: N/a Unit Of Measure:	1
Mounting Facility Type And Quantity: 2 unthreaded hole single mounting facility Mounting Facility Pattern: In-line single mounting facility Nonpile-up Main Contact Arrangement: 2 pole, double throw, one position momentary Time Delay: 0.10 seconds fixed operate time Operating Voltage Rating And Type At Specificationified Temp: 24.5 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 2.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 30.0 dc Terminal Type And Quantity: 8 pin all functions Shelf Life: N/a Unit Of Measure:	Duty Type:
2 unthreaded hole single mounting facility Mounting Facility Pattern: In-line single mounting facility Nonpile-up Main Contact Arrangement: 2 pole, double throw, one position momentary Time Delay: 0.10 seconds fixed operate time Operating Voltage Rating And Type At Specificationified Temp: 24.5 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 2.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 30.0 dc Terminal Type And Quantity: 8 pin all functions Shelf Life: N/a Unit Of Measure:	Continuous
Mounting Facility Pattern: In-line single mounting facility Nonpile-up Main Contact Arrangement: 2 pole, double throw, one position momentary Time Delay: 0.10 seconds fixed operate time Operating Voltage Rating And Type At Specificationified Temp: 24.5 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 2.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 30.0 dc Terminal Type And Quantity: 8 pin all functions Shelf Life: N/a Unit Of Measure:	Mounting Facility Type And Quantity:
In-line single mounting facility Nonpile-up Main Contact Arrangement: 2 pole, double throw, one position momentary Time Delay: 0.10 seconds fixed operate time Operating Voltage Rating And Type At Specificationified Temp: 24.5 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 2.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 30.0 dc Terminal Type And Quantity: 8 pin all functions Shelf Life: N/a Unit Of Measure:	2 unthreaded hole single mounting facility
Nonpile-up Main Contact Arrangement: 2 pole, double throw, one position momentary Time Delay: 0.10 seconds fixed operate time Operating Voltage Rating And Type At Specificationified Temp: 24.5 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 2.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 30.0 dc Terminal Type And Quantity: 8 pin all functions Shelf Life: N/a Unit Of Measure:	Mounting Facility Pattern:
2 pole, double throw, one position momentary Time Delay: 0.10 seconds fixed operate time Operating Voltage Rating And Type At Specificationified Temp: 24.5 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 2.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 30.0 dc Terminal Type And Quantity: 8 pin all functions Shelf Life: N/a Unit Of Measure:	In-line single mounting facility
Time Delay: 0.10 seconds fixed operate time Operating Voltage Rating And Type At Specificationified Temp: 24.5 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 2.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 30.0 dc Terminal Type And Quantity: 8 pin all functions Shelf Life: N/a Unit Of Measure:	Nonpile-up Main Contact Arrangement:
0.10 seconds fixed operate time Operating Voltage Rating And Type At Specificationified Temp: 24.5 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 2.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 30.0 dc Terminal Type And Quantity: 8 pin all functions Shelf Life: N/a Unit Of Measure:	2 pole, double throw, one position momentary
Operating Voltage Rating And Type At Specificationified Temp: 24.5 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 2.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 30.0 dc Terminal Type And Quantity: 8 pin all functions Shelf Life: N/a Unit Of Measure:	Time Delay:
24.5 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 2.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 30.0 dc Terminal Type And Quantity: 8 pin all functions Shelf Life: N/a Unit Of Measure:	0.10 seconds fixed operate time
Main Contact Load Current Rating At Maximum Rated Voltage: 2.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 30.0 dc Terminal Type And Quantity: 8 pin all functions Shelf Life: N/a Unit Of Measure:	Operating Voltage Rating And Type At Specificationified Temp:
2.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 30.0 dc Terminal Type And Quantity: 8 pin all functions Shelf Life: N/a Unit Of Measure:	24.5 volts dc 25 degrees celsius single winding
Main Contact Maximum Voltage Rating In Volts: 30.0 dc Terminal Type And Quantity: 8 pin all functions Shelf Life: N/a Unit Of Measure:	Main Contact Load Current Rating At Maximum Rated Voltage:
30.0 dc Terminal Type And Quantity: 8 pin all functions Shelf Life: N/a Unit Of Measure:	2.0 amperes dc resistive load
Terminal Type And Quantity: 8 pin all functions Shelf Life: N/a Unit Of Measure:	Main Contact Maximum Voltage Rating In Volts:
8 pin all functions Shelf Life: N/a Unit Of Measure:	30.0 dc
Shelf Life: N/a Unit Of Measure:	Terminal Type And Quantity:
N/a Unit Of Measure:	8 pin all functions
Unit Of Measure:	Shelf Life:
	N/a
Demilitarization:	Unit Of Measure:
Demilitarization:	
	Demilitarization:
No	No
Fiin	Fiig:
i iigi	-

A03300