NSN 5945-00-403-2532

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-403-2532

Thr	ead Class:		
2a s	2a single mounting facility		
Overall Length:			
1.01	5 inches		
Cen	ter To Center Distance Between Mounting Facilities Parallel To Length:		
0.62	25 inches single mounting facility		
Ove	erall Height:		
1.72	22 inches		
Ove	erall Width:		
0.51	5 inches		
Env	rironmental Protection:		
Heri	metic		
Win	ding Quantity:		
1			
Coi	Quantity:		
1			
Win	ding Dc Resistance Rating:		
320	.0 ohms single winding		
Dut	y Type:		
Con	itinuous		
Mounting Facility Type And Quantity:			
2 threaded stud single mounting facility			
Fea	tures Provided:		
Pola	arized		
Cub	oic Measure:		
0.90	00 cubic inches		
Thr	eady Qty Per Inch (tpi):		
32 s	single mounting facility		
Thr	ead Size:		
0.13	88 inches single mounting facility		
Mou	unting Facility Pattern:		
In-li	ne single mounting facility		
Non	pile-up Main Contact Arrangement:		
2 pc	ole, double throw, one position momentary		
Operating Voltage Rating And Type At Specificationified Temp:			
28.0 volts dc 25 degrees celsius single winding			
Main Contact Load Current Rating At Maximum Rated Voltage:			
3.0	amperes ac resistive load and 3.0 amperes dc resistive load		
Mai	n Contact Maximum Voltage Rating In Volts:		
115	.0 ac and 28.0 dc		
Thre	ead Series Designator:		

Unc single mounting facility

NSN 5945-00-403-2532

Electromagnetic Relay - Page 2 of 2



Terminal T	Type And	Quantity:
------------	----------	-----------

8 wire hook all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300