## NSN 5945-00-403-3905

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-403-3905

**Overall Length:** 

0.507 inches

**Overall Diameter:** 

0.335 inches

Case Material:

Metal

**Environmental Protection:** 

Hermetic

**Fragility Factor:** 

Moderately rugged

Winding Quantity:

1

**Coil Quantity:** 

1

Winding Dc Resistance Rating:

1.404 kilohms single winding and 1.716 kilohms single winding

**Duty Type:** 

Continuous

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

1 plug-in terminal single mounting facility

Storage Type:

General purpose warehouse

Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

### Time Delay:

0.003 seconds fixed operate time

**Operating Voltage Rating And Type At Specificationified Temp:** 

26.5 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

100.0 milliamperes dc lamp load

## Main Contact Maximum Voltage Rating In Volts:

28.0 dc

#### **Test Data Document:**

81349-mil-r-5757 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Terminal Type And Quantity:**

8 pin all functions

**Specification Data:** 

81349-mil-r-5757/40 government specification

Shelf Life:

# NSN 5945-00-403-3905

Electromagnetic Relay - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A03300

