## NSN 5945-00-403-3905

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-403-3905

view Online at https://aerobasegroup.com/hsn/5945-00-403-3905
Overall Length:
0.507 inches
Overall Diameter:
0.335 inches
Case Material:
Metal
Environmental Protection:
Hermetic
Fragility Factor:
Moderately rugged
Winding Quantity:
1
Coil Quantity:
1
Winding Dc Resistance Rating:
1.404 kilohms single winding and 1.716 kilohms single winding
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
1 plug-in terminal single mounting facility
Storage Type:
General purpose warehouse
Nonpile-up Main Contact Arrangement:
2 pole, double throw, one position momentary
Time Delay:
0.003 seconds fixed operate time
Operating Voltage Rating And Type At Specificationified Temp:
26.5 volts dc 25 degrees celsius single winding
Main Contact Load Current Rating At Maximum Rated Voltage:
100.0 milliamperes dc lamp load
Main Contact Maximum Voltage Rating In Volts:
28.0 dc
Test Data Document:
81349-mil-r-5757 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
8 pin all functions
Specification Data:

N/a

Shelf Life:

81349-mil-r-5757/40 government specification

## NSN 5945-00-403-3905

Electromagnetic Relay - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A03300