NSN 5945-00-403-4057

Electromagnetic Relay - Page 1 of 2

Thread Class:



View Online at https://aerobasegroup.com/nsn/5945-00-403-4057

2a single mounting facility
Thread Direction:
Right-hand single mounting facility
Thread Length:
0.375 inches single mounting facility
Overall Length:
1.625 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.938 inches single mounting facility
Overall Height:
2.437 inches
Overall Width:
1.406 inches
Case Material:
Metal
Environmental Protection:
Hermetic
Fragility Factor:
Moderately rugged
Frequency In Hertz:
60.0
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
3 threaded stud single mounting facility
Storage Type:
General purpose warehouse
Cubic Measure:
5.568 cubic inches
Thready Qty Per Inch (tpi):
32 single mounting facility
Thread Size:
0.138 inches single mounting facility

NSN 5945-00-403-4057

Electromagnetic Relay - Page 2 of 2



Mounting Facility Pattern:

Triangle single mounting facility

Nonpile-up Main Contact Arrangement:

2 pole, single throw, normally open, momentary action

Time Delay:

0.05 seconds fixed operate time

Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:

1.188 inches single mounting facility

Operating Voltage Rating And Type At Specificationified Temp:

115.0 volts ac 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

5.0 amperes ac resistive load and 5.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Thread Series Designator:

Unc single mounting facility

Terminal Type And Quantity:

6 tab, solder lug all functions

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A03300