NSN 5945-00-405-3906

Electromagnetic Relay - Page 1 of 2

81349-mil-r-5757/40 government specification



View Online at https://aerobasegroup.com/nsn/5945-00-405-3906

Overall Length:		
0.507 inches		
Overall Diameter:		
0.335 inches		
Case Material:		
Metal		
Environmental Protection:		
Hermetic		
Fragility Factor:		
Moderately rugged		
Winding Quantity:		
1		
Purpose For Which Designed:		
General		
Coil Quantity:		
1		
Winding Dc Resistance Rating:		
351.0 ohms single winding and 429.0 ohms single winding		
Duty Type:		
Continuous		
Arc Quenching Method:		
Air		
Mounting Facility Type And Quantity:		
1 plug-in terminal single mounting facility		
Storage Type:		
General purpose warehouse		
Nonpile-up Main Contact Arrangement:		
2 pole, double throw, one position momentary		
Time Delay:		
0.003 seconds fixed operate time		
Operating Voltage Rating And Type At Specificationified Temp:		
12.0 volts dc 25 degrees celsius single winding		
Main Contact Load Current Rating At Maximum Rated Voltage:		
100.0 milliamperes dc lamp load		
Main Contact Maximum Voltage Rating In Volts:		
28.0 dc		
Test Data Document:		
81349-mil-r-5757 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification		
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain		
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).		
Terminal Type And Quantity:		
8 pin all functions		
Specification Data:		

NSN 5945-00-405-3906

Electromagnetic Relay - Page 2 of 2



She	lf I	Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300