## NSN 5945-00-407-2783

Electromagnetic Relay - Page 1 of 2

**Thread Class:** 



View Online at https://aerobasegroup.com/nsn/5945-00-407-2783

2a single mounting facility
Thread Direction:
Right-hand single mounting facility
Thread Length:
0.313 inches single mounting facility
Overall Length:
1.813 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.562 inches single mounting facility
Overall Height:
1.750 inches
Overall Width:
1.313 inches
Case Material:
Metal
Environmental Protection:
Hermetic
Fragility Factor:
Moderately rugged
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Winding Dc Resistance Rating:
240.0 ohms single winding
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
2 threaded stud single mounting facility
Storage Type:
General purpose warehouse
Cubic Measure:
4.167 cubic inches
Thready Qty Per Inch (tpi):
32 single mounting facility
Thread Size:
0.138 inches single mounting facility

## NSN 5945-00-407-2783

Electromagnetic Relay - Page 2 of 2



## Mounting Facility Pattern:

In-line single mounting facility

**Nonpile-up Main Contact Arrangement:** 

6 pole, double throw, one position momentary

Time Delay:

0.01 seconds fixed operate time

**Operating Voltage Rating And Type At Specificationified Temp:** 

26.5 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

2.0 amperes ac resistive load and 5.0 amperes dc resistive load

**Main Contact Maximum Voltage Rating In Volts:** 

115.0 ac and 29.0 dc

**Thread Series Designator:** 

Unc single mounting facility

**Terminal Type And Quantity:** 

20 wire hook all functions

Shelf Life:

N/a

**Unit Of Measure:** 

**Demilitarization:** 

No

Fiig:

A03300