NSN 5945-00-410-5107



E	lectromagnetic Relay - Page 1 of 2	AC
Vi	ew Online at https://aerobasegroup.com/nsn/5945-00-410-5107	
Tł	nread Class:	
2b	single mounting facility	
Tł	nread Direction:	
Ri	ight-hand single mounting facility	
O	verall Length:	
0.9	950 inches	
O ₁	verall Height:	
0.4	413 inches	
O	verall Width:	
0.0	690 inches	
Ca	ase Material:	
Pl	astic	
Fr	ragility Factor:	
M	oderately rugged	
W	inding Quantity:	
1		
Pι	urpose For Which Designed:	
G	eneral	
Co	oil Quantity:	
1		
W	inding Dc Resistance Rating:	
10	0.0 kilohms single winding	
Dı	uty Type:	
Co	ontinuous	
Aı	rc Quenching Method:	
Ai	r	
M	ounting Facility Type And Quantity:	

1 threaded hole single mounting facility

Storage Type:

General purpose warehouse

Features Provided:

Polarized

Cubic Measure:

0.271 cubic inches

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.138 inches single mounting facility

Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

Operating Current Rating And Type:

9.0 milliamperes ac single winding

NSN 5945-00-410-5107

Electromagnetic Relay - Page 2 of 2



Operating Voltage Rating And Type At Specificationified Temp:

240.0 volts ac 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

8.0 amperes ac resistive load and 8.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

110.0 ac and 30.0 dc

Thread Series Designator:

Unc single mounting facility

Terminal Type And Quantity:

8 quick disconnect, male all functions

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A03300