

View Online at <https://aerobasegroup.com/nsn/5945-00-412-0671>

Thread Class:

2a single mounting facility

Thread Direction:

Right-hand single mounting facility

Thread Length:

0.312 inches single mounting facility

Overall Length:

1.109 inches

Overall Height:

1.593 inches

Overall Width:

0.859 inches

Case Material:

Plastic

Environmental Protection:

Dustproof

Fragility Factor:

Moderately rugged

Contact Material:

Silver

Contact Surface Treatment:

Gold flash

Frequency In Hertz:

60.0

Winding Quantity:

1

Coil Quantity:

1

Winding Dc Resistance Rating:

10.5 ohms single winding

Duty Type:

Continuous

Mounting Facility Type And Quantity:

1 threaded stud single mounting facility

Storage Type:

General purpose warehouse

Thready Qty Per Inch (tpi):

48 single mounting facility

Thread Size:

0.099 inches single mounting facility

Nonpile-up Main Contact Arrangement:

4 pole, double throw, one position momentary

Operating Current Rating And Type:

200.0 milliamperes ac single winding

Operating Voltage Rating And Type At Specificationified Temp:

6.0 volts ac 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

3.0 amperes ac resistive load and 3.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

120.0 ac and 30.0 dc

Energizing Element Power Rating:

1.2 volts-amperes

Precious Material And Location:

Contacts silver and contact surfaces gold

Precious Material:

Silver and gold

Thread Series Designator:

Unc single mounting facility

Terminal Type And Quantity:

14 tab, solder lug all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300