NSN 5945-00-416-4843

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-416-4843

View Online at https://aerobasegroup.com/nsn/5945-00-416-4843
Thread Class:
2a single mounting facility
Thread Direction:
Right-hand single mounting facility
Overall Length:
1.531 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.187 inches single mounting facility
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.187 inches single mounting facility
Overall Height:
2.087 inches
Overall Width:
1.531 inches
Case Material:
Metal
Environmental Protection:
Hermetic
Fragility Factor:
Moderately rugged
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Winding Dc Resistance Rating:
640.0 ohms single winding
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
4 threaded stud single mounting facility
Storage Type:
General purpose warehouse
Cubic Measure:
4.891 cubic inches
Thready Qty Per Inch (tpi):
32 single mounting facility

Thread Size:

0.138 inches single mounting facility

NSN 5945-00-416-4843

Electromagnetic Relay - Page 2 of 2



Mounting Facility Pattern:

Rectangular single mounting facility

Nonpile-up Main Contact Arrangement:

3 pole, single throw, normally open, momentary action

Time Delay:

0.02 seconds fixed operate time

Operating Voltage Rating And Type At Specificationified Temp:

50.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

20.0 amperes ac motor load and 20.0 amperes dc motor load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Thread Series Designator:

Unc single mounting facility

Terminal Type And Quantity:

8 wire hook all functions

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A03300