NSN 5945-00-421-0564

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-421-0564

Thread Class:
2a single mounting facility
Thread Direction:
Right-hand single mounting facility
Overall Length:
1.531 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.187 inches single mounting facility
Center To Center Distance Between Mounting Facilities Parallel To Width:
0.687 inches single mounting facility
Overall Height:
2.187 inches
Overall Width:
1.032 inches
Case Material:
Metal
Environmental Protection:
Hermetic
Fragility Factor:
Moderately rugged
Winding Quantity:
2
Purpose For Which Designed:
General
Coil Quantity:
2
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
4 threaded stud single mounting facility
Storage Type:
General purpose warehouse
Features Provided:
Latching contacts
Thready Qty Per Inch (tpi):
32 single mounting facility
Thread Size:
0.138 inches single mounting facility
Mounting Facility Pattern:

Rectangular single mounting facility

NSN 5945-00-421-0564

Electromagnetic Relay - Page 2 of 2



Nonpile-up Main Contact Arrangement: 4 pole, double throw, one position momentary **Time Delay:** 0.025 seconds fixed operate time **Operating Voltage Rating And Type At Specificationified Temp:** 28.0 volts dc 25 degrees celsius all windings Main Contact Load Current Rating At Maximum Rated Voltage: 1.5 amperes ac motor load and 1.5 amperes dc motor load Main Contact Maximum Voltage Rating In Volts: 115.0 ac and 28.0 dc **Test Data Document:** 81349-mil-r-6106 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Thread Series Designator:** Unc single mounting facility **Terminal Type And Quantity:** 16 wire hook all functions **Specification Data:** 96906-ms25467 government standard Shelf Life: N/a Unit Of Measure: **Demilitarization:** No Fiig: A03300 Mil-std (military Standard): Mil-r-6106 spec.