NSN 5945-00-425-6227

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-425-6227

| Overall Length: |
|---|
| 1.885 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 1.406 inches single mounting facility |
| Overall Height: |
| 0.950 inches |
| Overall Width: |
| 1.718 inches |
| Environmental Protection: |
| Hermetic |
| Unthreaded Mounting Hole Diameter: |
| 0.166 inches single mounting facility |
| Center To Center Distance Between Mounting Facilities Parallel To Height: |
| 0.500 inches single mounting facility |
| Winding Quantity: |
| 2 |
| Coil Quantity: |
| 2 |
| Winding Dc Resistance Rating: |
| 500.0 ohms all windings |
| Duty Type: |
| Continuous |
| Arc Quenching Method: |
| Inert gas |
| Mounting Facility Type And Quantity: |
| 4 unthreaded hole single mounting facility |
| Pile-up Main Contact Form Arrangement: |
| 4c |
| Features Provided: |
| Polarized and latching contacts |
| Mounting Facility Pattern: |
| Rectangular single mounting facility |
| Nonpile-up Main Contact Arrangement: |
| 4 pole, double throw, one position momentary |
| Operating Voltage Rating And Type At Specificationified Temp: |
| 28.0 volts dc 25 degrees celsius all windings |
| Main Contact Load Current Rating At Maximum Rated Voltage: |
| 3.0 amperes ac resistive load |
| Main Contact Maximum Voltage Rating In Volts: |
| 115.0 ac |

Terminal Type And Quantity: 16 wire hook all functions

NSN 5945-00-425-6227

Electromagnetic Relay - Page 2 of 2



| | Life: |
|--|-------|
| | |
| | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300