# NSN 5945-00-426-6979

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-426-6979

### **Overall Length:**

0.375 inches

**Overall Diameter:** 

0.370 inches

# Case Material:

Metal

#### **Environmental Protection:**

Hermetic

### Fragility Factor:

Moderately rugged

#### Winding Quantity:

1

#### Purpose For Which Designed:

General

#### **Coil Quantity:**

1

## Winding Dc Resistance Rating:

229.5 ohms single winding and 280.5 ohms single winding

#### **Duty Type:**

Continuous

## Arc Quenching Method:

Air

#### Mounting Facility Type And Quantity:

1 terminal single mounting facility

#### Storage Type:

General purpose warehouse

#### Nonpile-up Main Contact Arrangement:

1 pole, double throw, one position momentary

#### **Operating Current Rating And Type:**

23.5 milliamperes dc single winding

#### Time Delay:

0.004 seconds fixed operate time

#### **Operating Voltage Rating And Type At Specificationified Temp:**

6.0 volts dc 25 degrees celsius single winding

#### Main Contact Load Current Rating At Maximum Rated Voltage:

2.0 amperes dc resistive load

### Main Contact Maximum Voltage Rating In Volts:

28.0 dc

# **Energizing Element Power Rating:**

40.0 milliwatts

# **Test Data Document:**

81349-mil-r-5757 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# NSN 5945-00-426-6979

Electromagnetic Relay - Page 2 of 2



Terminal Type And Quantity:

5 wire lead all functions

#### **Specification Data:**

81349-mil-r-5757/69 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300