## NSN 5945-00-428-6353

Electromagnetic Relay - Page 1 of 1



Online .//~ n/nen/5 Vi 8-6353

View Online at https://aerobasegroup.com/nsn/5945-00-428-6353
Overall Length:
4.766 inches
Overall Height:
3.812 inches
Overall Width:
4.125 inches
Environmental Protection:
Dustproof
Winding Quantity:
1
Coil Quantity:
1
Winding Dc Resistance Rating:
1.7 ohms single winding
Duty Type:
Intermittent
Operating Voltage Rating And Type At Specificationified Temp:
Operating Voltage Rating And Type At Specificationified Temp: 12.0 volts dc 25 degrees celsius single winding
12.0 volts dc 25 degrees celsius single winding
12.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage:
<ul> <li>12.0 volts dc 25 degrees celsius single winding</li> <li>Main Contact Load Current Rating At Maximum Rated Voltage:</li> <li>500.0 amperes dc inductive load</li> </ul>
<ul> <li>12.0 volts dc 25 degrees celsius single winding</li> <li>Main Contact Load Current Rating At Maximum Rated Voltage:</li> <li>500.0 amperes dc inductive load</li> <li>Main Contact Maximum Voltage Rating In Volts:</li> </ul>
<ul> <li>12.0 volts dc 25 degrees celsius single winding</li> <li>Main Contact Load Current Rating At Maximum Rated Voltage:</li> <li>500.0 amperes dc inductive load</li> <li>Main Contact Maximum Voltage Rating In Volts:</li> <li>12.0 dc</li> </ul>
<ul> <li>12.0 volts dc 25 degrees celsius single winding</li> <li>Main Contact Load Current Rating At Maximum Rated Voltage:</li> <li>500.0 amperes dc inductive load</li> <li>Main Contact Maximum Voltage Rating In Volts:</li> <li>12.0 dc</li> <li>Special Features:</li> </ul>
<ul> <li>12.0 volts dc 25 degrees celsius single winding</li> <li>Main Contact Load Current Rating At Maximum Rated Voltage:</li> <li>500.0 amperes dc inductive load</li> <li>Main Contact Maximum Voltage Rating In Volts:</li> <li>12.0 dc</li> <li>Special Features:</li> <li>Fungus and moisture proof</li> </ul>
<ul> <li>12.0 volts dc 25 degrees celsius single winding</li> <li>Main Contact Load Current Rating At Maximum Rated Voltage:</li> <li>500.0 amperes dc inductive load</li> <li>Main Contact Maximum Voltage Rating In Volts:</li> <li>12.0 dc</li> <li>Special Features:</li> <li>Fungus and moisture proof</li> <li>Shelf Life:</li> </ul>
12.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 500.0 amperes dc inductive load Main Contact Maximum Voltage Rating In Volts: 12.0 dc Special Features: Fungus and moisture proof Shelf Life: N/a
12.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 500.0 amperes dc inductive load Main Contact Maximum Voltage Rating In Volts: 12.0 dc Special Features: Fungus and moisture proof Shelf Life: N/a
12.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 500.0 amperes dc inductive load Main Contact Maximum Voltage Rating In Volts: 12.0 dc Special Features: Fungus and moisture proof Shelf Life: N/a Unit Of Measure:
12.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 500.0 amperes dc inductive load Main Contact Maximum Voltage Rating In Volts: 12.0 dc Special Features: Fungus and moisture proof Shelf Life: N/a Unit Of Measure:  Demilitarization:
12.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 500.0 amperes dc inductive load Main Contact Maximum Voltage Rating In Volts: 12.0 dc Special Features: Fungus and moisture proof Shelf Life: N/a Unit Of Measure:  Demilitarization: No