## NSN 5945-00-431-4885

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-431-4885

Thread Class:
2b single mounting facility
Overall Length:
2.046 inches
Overall Height:
1.140 inches
Overall Width:
1.546 inches
Frequency In Hertz:
60.0
Winding Quantity:
1
Coil Quantity:
1
Winding Dc Resistance Rating:
24.0 ohms single winding and 34.0 ohms single winding
Duty Type:
Continuous
Mounting Facility Type And Quantity:
1 threaded hole single mounting facility
Pile-up Auxiliary Contact Form Arrangement:
2c
Three de Ote Ber hack (to b)
Thready Qty Per Inch (tpi):
32 single mounting facility
32 single mounting facility
32 single mounting facility  Thread Size:
32 single mounting facility  Thread Size:  0.164 inches single mounting facility
32 single mounting facility  Thread Size:  0.164 inches single mounting facility  Nonpile-up Main Contact Arrangement:
32 single mounting facility  Thread Size: 0.164 inches single mounting facility  Nonpile-up Main Contact Arrangement: 2 pole, double throw, one position momentary
32 single mounting facility  Thread Size: 0.164 inches single mounting facility  Nonpile-up Main Contact Arrangement: 2 pole, double throw, one position momentary  Time Delay:
32 single mounting facility  Thread Size:  0.164 inches single mounting facility  Nonpile-up Main Contact Arrangement:  2 pole, double throw, one position momentary  Time Delay:  0.05 seconds fixed release time
32 single mounting facility  Thread Size: 0.164 inches single mounting facility  Nonpile-up Main Contact Arrangement: 2 pole, double throw, one position momentary  Time Delay: 0.05 seconds fixed release time  Operating Voltage Rating And Type At Specificationified Temp:
32 single mounting facility  Thread Size:  0.164 inches single mounting facility  Nonpile-up Main Contact Arrangement:  2 pole, double throw, one position momentary  Time Delay:  0.05 seconds fixed release time  Operating Voltage Rating And Type At Specificationified Temp:  24.0 volts ac 25 degrees celsius single winding
32 single mounting facility  Thread Size: 0.164 inches single mounting facility  Nonpile-up Main Contact Arrangement: 2 pole, double throw, one position momentary  Time Delay: 0.05 seconds fixed release time  Operating Voltage Rating And Type At Specificationified Temp: 24.0 volts ac 25 degrees celsius single winding  Main Contact Load Current Rating At Maximum Rated Voltage:
Thread Size:  0.164 inches single mounting facility  Nonpile-up Main Contact Arrangement:  2 pole, double throw, one position momentary  Time Delay:  0.05 seconds fixed release time  Operating Voltage Rating And Type At Specificationified Temp:  24.0 volts ac 25 degrees celsius single winding  Main Contact Load Current Rating At Maximum Rated Voltage:  10.0 amperes ac resistive load
Thread Size: 0.164 inches single mounting facility Nonpile-up Main Contact Arrangement: 2 pole, double throw, one position momentary Time Delay: 0.05 seconds fixed release time Operating Voltage Rating And Type At Specificationified Temp: 24.0 volts ac 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 10.0 amperes ac resistive load Main Contact Maximum Voltage Rating In Volts:
Thread Size:  0.164 inches single mounting facility  Nonpile-up Main Contact Arrangement:  2 pole, double throw, one position momentary  Time Delay:  0.05 seconds fixed release time  Operating Voltage Rating And Type At Specificationified Temp:  24.0 volts ac 25 degrees celsius single winding  Main Contact Load Current Rating At Maximum Rated Voltage:  10.0 amperes ac resistive load  Main Contact Maximum Voltage Rating In Volts:  115.0 ac
Thread Size:  0.164 inches single mounting facility  Nonpile-up Main Contact Arrangement:  2 pole, double throw, one position momentary  Time Delay:  0.05 seconds fixed release time  Operating Voltage Rating And Type At Specificationified Temp:  24.0 volts ac 25 degrees celsius single winding  Main Contact Load Current Rating At Maximum Rated Voltage:  10.0 amperes ac resistive load  Main Contact Maximum Voltage Rating In Volts:  115.0 ac  Thread Series Designator:
Thread Size:  0.164 inches single mounting facility  Nonpile-up Main Contact Arrangement:  2 pole, double throw, one position momentary  Time Delay:  0.05 seconds fixed release time  Operating Voltage Rating And Type At Specificationified Temp:  24.0 volts ac 25 degrees celsius single winding  Main Contact Load Current Rating At Maximum Rated Voltage:  10.0 amperes ac resistive load  Main Contact Maximum Voltage Rating In Volts:  115.0 ac  Thread Series Designator:  Unc single mounting facility

N/a

## NSN 5945-00-431-4885

Electromagnetic Relay - Page 2 of 2



**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A03300