NSN 5945-00-433-6461

Electromagnetic Relay - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5945-00-433-6461

| Overall Length: |
|-------------------------------------------------------------------------------------------------------------------|
| 7.750 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 2.000 inches single mounting facility |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 2.000 inches single mounting facility |
| Overall Height: |
| 3.000 inches |
| Overall Width: |
| 4.375 inches |
| Unthreaded Mounting Hole Diameter: |
| 0.190 inches single mounting facility |
| Frequency In Hertz: |
| 60.0 |
| Winding Quantity: |
| 1 |
| Coil Quantity: |
| 1 |
| Duty Type: |
| Continuous |
| Mounting Facility Type And Quantity: |
| 2 unthreaded hole single mounting facility |
| Mounting Facility Pattern: |
| Diagonal single mounting facility |
| Nonpile-up Main Contact Arrangement: |
| 1 pole, single throw, normally open, momentary action and 1 pole, single throw, normally closed, momentary action |
| Operating Current Rating And Type: |
| 9.0 amperes ac single winding |
| Main Contact Load Current Rating At Maximum Rated Voltage: |
| 1.5 amperes ac resistive load and 100.0 milliamperes dc resistive load |
| Main Contact Maximum Voltage Rating In Volts: |
| 600.0 ac and 550.0 dc |
| Terminal Type And Quantity: |
| 4 pin all functions |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| <u></u> |
| Demilitarization: |
| No |
| Fiig: |
| A03300 |