## NSN 5945-00-434-3392

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-434-3392

**Thread Class:** 2a single mounting facility **Overall Length:** 2.625 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 1.187 inches single mounting facility **Center To Center Distance Between Mounting Facilities Parallel To Width:** 1.187 inches single mounting facility **Overall Height:** 1.531 inches **Overall Width:** 1.531 inches **Environmental Protection:** Hermetic Frequency In Hertz: 60.0 **Winding Quantity:** 2 **Coil Quantity:** Winding Dc Resistance Rating: 800.0 ohms single winding **Duty Type:** Continuous **Mounting Facility Type And Quantity:** 4 threaded stud single mounting facility **Features Provided:** Polarized and latching contacts Thready Qty Per Inch (tpi): 32 single mounting facility **Thread Size:** 0.138 inches single mounting facility **Mounting Facility Pattern:** Rectangular single mounting facility **Nonpile-up Main Contact Arrangement:** 6 pole, double throw, one position momentary Time Delay: 0.02 seconds fixed operate time Operating Voltage Rating And Type At Specificationified Temp:

115.0 volts ac 25 degrees celsius all windings

Main Contact Load Current Rating At Maximum Rated Voltage:

5.0 amperes ac resistive load and 5.0 amperes dc resistive load

## NSN 5945-00-434-3392

Electromagnetic Relay - Page 2 of 2



Main Contact Maximum	Voltage Rating In Volts
115.0 ac and 28.0 dc	

**Thread Series Designator:** 

Unc single mounting facility

**Terminal Type And Quantity:** 

22 pin all functions

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_\_

Demilitarization:

No

Fiig:

A03300