## NSN 5945-00-435-9520

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-435-9520

Overall Length:
0.900 inches
Overall Height:
0.400 inches
Overall Width:
0.800 inches
Environmental Protection:
Hermetic
Fragility Factor:
Moderately rugged
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Winding Dc Resistance Rating:
600.0 ohms single winding
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
Mounting Facility Type And Quantity:  1 plug-in terminal single mounting facility
, , , ,
1 plug-in terminal single mounting facility
1 plug-in terminal single mounting facility  Storage Type:
1 plug-in terminal single mounting facility  Storage Type:  General purpose warehouse
1 plug-in terminal single mounting facility  Storage Type:  General purpose warehouse  Cubic Measure:
1 plug-in terminal single mounting facility  Storage Type: General purpose warehouse  Cubic Measure:  0.288 cubic inches
1 plug-in terminal single mounting facility  Storage Type: General purpose warehouse  Cubic Measure: 0.288 cubic inches  Nonpile-up Main Contact Arrangement:
1 plug-in terminal single mounting facility  Storage Type:  General purpose warehouse  Cubic Measure:  0.288 cubic inches  Nonpile-up Main Contact Arrangement:  2 pole, double throw, one position momentary
1 plug-in terminal single mounting facility  Storage Type: General purpose warehouse  Cubic Measure: 0.288 cubic inches  Nonpile-up Main Contact Arrangement: 2 pole, double throw, one position momentary  Time Delay:
1 plug-in terminal single mounting facility  Storage Type: General purpose warehouse  Cubic Measure: 0.288 cubic inches  Nonpile-up Main Contact Arrangement: 2 pole, double throw, one position momentary  Time Delay: 0.005 seconds fixed operate time
1 plug-in terminal single mounting facility  Storage Type: General purpose warehouse  Cubic Measure: 0.288 cubic inches  Nonpile-up Main Contact Arrangement: 2 pole, double throw, one position momentary  Time Delay: 0.005 seconds fixed operate time  Operating Voltage Rating And Type At Specificationified Temp:
1 plug-in terminal single mounting facility  Storage Type: General purpose warehouse  Cubic Measure: 0.288 cubic inches  Nonpile-up Main Contact Arrangement: 2 pole, double throw, one position momentary  Time Delay: 0.005 seconds fixed operate time  Operating Voltage Rating And Type At Specificationified Temp: 13.5 volts dc 25 degrees celsius single winding
1 plug-in terminal single mounting facility  Storage Type: General purpose warehouse  Cubic Measure: 0.288 cubic inches  Nonpile-up Main Contact Arrangement: 2 pole, double throw, one position momentary  Time Delay: 0.005 seconds fixed operate time  Operating Voltage Rating And Type At Specificationified Temp: 13.5 volts dc 25 degrees celsius single winding  Main Contact Load Current Rating At Maximum Rated Voltage:
1 plug-in terminal single mounting facility  Storage Type: General purpose warehouse  Cubic Measure: 0.288 cubic inches  Nonpile-up Main Contact Arrangement: 2 pole, double throw, one position momentary  Time Delay: 0.005 seconds fixed operate time  Operating Voltage Rating And Type At Specificationified Temp: 13.5 volts dc 25 degrees celsius single winding  Main Contact Load Current Rating At Maximum Rated Voltage: 1.0 amperes dc inductive load
1 plug-in terminal single mounting facility  Storage Type: General purpose warehouse  Cubic Measure: 0.288 cubic inches  Nonpile-up Main Contact Arrangement: 2 pole, double throw, one position momentary  Time Delay: 0.005 seconds fixed operate time  Operating Voltage Rating And Type At Specificationified Temp: 13.5 volts dc 25 degrees celsius single winding  Main Contact Load Current Rating At Maximum Rated Voltage: 1.0 amperes dc inductive load  Main Contact Maximum Voltage Rating In Volts:
1 plug-in terminal single mounting facility  Storage Type: General purpose warehouse  Cubic Measure: 0.288 cubic inches  Nonpile-up Main Contact Arrangement: 2 pole, double throw, one position momentary  Time Delay: 0.005 seconds fixed operate time  Operating Voltage Rating And Type At Specificationified Temp: 13.5 volts dc 25 degrees celsius single winding  Main Contact Load Current Rating At Maximum Rated Voltage: 1.0 amperes dc inductive load  Main Contact Maximum Voltage Rating In Volts: 115.0 ac and 28.0 dc

N/a

## NSN 5945-00-435-9520

Electromagnetic Relay - Page 2 of 2



		eas	

--

Demilitarization:

No

Fiig:

A03300