

View Online at <https://aerobasegroup.com/nsn/5945-00-436-6264>

Thread Class:

2a single mounting facility

Thread Direction:

Right-hand single mounting facility

Overall Length:

1.080 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.488 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.220 inches single mounting facility

Overall Height:

0.735 inches

Overall Width:

0.790 inches

Case Material:

Metal

Environmental Protection:

Hermetic

Fragility Factor:

Moderately rugged

Contact Material:

Silver

Contact Surface Treatment:

Gold

Winding Quantity:

1

Purpose For Which Designed:

General

Coil Quantity:

1

Winding Dc Resistance Rating:

600.0 ohms single winding

Duty Type:

Continuous

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

2 threaded stud single mounting facility

Storage Type:

General purpose warehouse

Cubic Measure:

0.627 cubic inches

Thready Qty Per Inch (tpi):

40 single mounting facility

Thread Size:

0.112 inches single mounting facility

Mounting Facility Pattern:

Diagonal single mounting facility

Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

Operating Current Rating And Type:

40.0 milliamperes dc single winding

Time Delay:

0.005 seconds fixed operate and release time

Operating Voltage Rating And Type At Specificationified Temp:

26.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

2.0 amperes ac resistive load and 2.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Precious Material And Location:

Contacts silver and contact surfaces gold

Precious Material:

Silver and gold

Thread Series Designator:

Unc single mounting facility

Terminal Type And Quantity:

8 wire hook all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A03300