## NSN 5945-00-450-1649

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-450-1649

**Thread Class:** 2a second mounting facility **Thread Length:** 0.375 inches second mounting facility **Overall Length:** 2.593 inches **Overall Height:** 1.437 inches **Overall Width:** 1.625 inches **Environmental Protection:** Hermetic Winding Quantity: **Coil Quantity:** Winding Dc Resistance Rating: 445.0 ohms single winding **Duty Type:** Continuous **Mounting Facility Type And Quantity:** 3 threaded stud second mounting facility **Thread Size:** 0.138 inches second mounting facility **Mounting Facility Pattern:** Triangle second mounting facility **Nonpile-up Main Contact Arrangement:** 4 pole, double throw, one position momentary Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle: 1.187 inches second mounting facility Operating Voltage Rating And Type At Specificationified Temp: 26.5 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 3.0 amperes ac resistive load and 3.0 amperes dc resistive load **Main Contact Maximum Voltage Rating In Volts:** 115.0 ac and 26.5 dc **Special Test Features:** Navord od41152 **Thread Series Designator:** Unc second mounting facility

8 pin all functions

**Terminal Type And Quantity:** 

## NSN 5945-00-450-1649

Electromagnetic Relay - Page 2 of 2



Reference Number Differentiating Characteris
--

As differentiated by special test features

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A03300