

View Online at <https://aerobasegroup.com/nsn/5945-00-450-3466>

**Thread Class:**

2a power takeoff facility stud

**Body Style:**

Cylindrical frame

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.812 inches

**Body Diameter:**

0.625 inches

**Mounting Slot Width:**

Between 0.104 inches and 0.170 inches

**Body Length:**

0.750 inches

**Case Material:**

Metal

**Case Surface Treatment:**

Any acceptable

**Environmental Protection:**

Any acceptable

**Maximum Operating Temp:**

140.0 degrees fahrenheit

**Mounting Base Width:**

1.000 inches

**Actuator Length:**

0.312 inches

**Actuator Diameter:**

0.062 inches

**Inclosure Type:**

Fully enclosed

**Magnetic Coil Quantity:**

1

**Duty Type:**

Continuous

**Terminal Location:**

End opposite actuator

**Voltage Rating In Volts:**

28.0 dc

**Mounting Facility Type And Quantity:**

1 bracket and 2 slot

**Current Rating:**

200.0 milliamperes

**Thready Qty Per Inch (tpi):**

80 power takeoff facility stud

**Actuator Stroke Type:**

Push

**Linear Force Delivered:**

9.50 ounces

**Power Takeoff Connection Type:**

External threads

**Energizing Stroke Maximum Length:**

0.050 inches

**Thread Size:**

0.060 inches power takeoff facility stud

**Mounting Facility Pattern:**

Two position in-line

**Thread Series Designator:**

Unf power takeoff facility stud

**Terminal Type And Quantity:**

2 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A134a0