NSN 5945-00-451-5975

Electromagnetic Relay - Page 1 of 2



| view Online at https://aerobasegroup.com/nsn/5945-00-451-5975 |
|---|
| Thread Class: |
| 2a single mounting facility |
| Thread Direction: |
| Right-hand single mounting facility |
| Overall Length: |
| 1.109 inches |
| Overall Height: |
| 1.593 inches |
| Overall Width: |
| 0.859 inches |
| Case Material: |
| Plastic |
| Contact Material: |
| Silver |
| Winding Quantity: |
| 1 |
| Coil Quantity: |
| 1 |
| Winding Dc Resistance Rating: |
| 160.0 ohms single winding |
| Duty Type: |
| Continuous |
| Mounting Facility Type And Quantity: |
| 1 threaded stud single mounting facility |
| Cubic Measure: |
| 1.682 cubic inches |
| Thready Qty Per Inch (tpi): |
| 48 single mounting facility |
| Thread Size: |
| 0.099 inches single mounting facility |
| Nonpile-up Main Contact Arrangement: |
| 4 pole, double throw, one position momentary |
| Time Delay: |
| 0.013 seconds fixed operate time |
| Operating Voltage Rating And Type At Specificationified Temp: |
| 12.0 volts dc 25 degrees celsius single winding |
| Main Contact Load Current Rating At Maximum Rated Voltage: |
| 3.0 amperes ac resistive load and 3.0 amperes dc resistive load |
| Main Contact Maximum Voltage Rating In Volts: |
| 120 0 ac and 30 0 dc |

Contacts silver

Precious Material And Location:

NSN 5945-00-451-5975

Electromagnetic Relay - Page 2 of 2



| Precious Material: |
|----------------------------------|
| Silver |
| Thread Series Designator: |
| Unc single mounting facility |
| Terminal Type And Quantity: |
| 14 tab, solder lug all functions |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

No Fiig: A03300