

View Online at <https://aerobasegroup.com/nsn/5945-00-451-6383>

Thread Class:

2b first mounting facility

Overall Length:

4.220 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.750 inches first mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.500 inches second mounting facility

Overall Height:

3.090 inches

Overall Width:

3.250 inches

Environmental Protection:

Dustproof

Unthreaded Mounting Hole Diameter:

0.199 inches second mounting facility

Frequency In Hertz:

60.0

Winding Quantity:

1

Coil Quantity:

1

Duty Type:

Continuous

Mounting Facility Type And Quantity:

6 unthreaded hole second mounting facility

Thread Size:

0.164 inches first mounting facility

Mounting Facility Pattern:

Rectangular second mounting facility

Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

Time Delay:

0.50 minutes adjustable operate time and 10.00 minutes adjustable operate time

Operating Voltage Rating And Type At Specificationified Temp:

70.0 volts ac 25 degrees celsius all windings

Main Contact Load Current Rating At Maximum Rated Voltage:

2.5 amperes ac resistive load and 1.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

480.0 ac and 110.0 dc

Special Features:

Operate time is variable, controlled pneumatically by a calibrated dial

Thread Series Designator:

Unc first mounting facility

Terminal Type And Quantity:

8 screw all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300