NSN 5945-00-458-7204

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-458-7204

Overall	Length:
---------	---------

1.940 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.562 inches single mounting facility

Overall Height:

1.320 inches

Overall Width:

1.880 inches

Environmental Protection:

Hermetic

Unthreaded Mounting Hole Diameter:

0.152 inches single mounting facility

Fragility Factor:

Moderately rugged

Winding Quantity:

1

Purpose For Which Designed:

General

Coil Quantity:

Winding Dc Resistance Rating:

270.0 ohms single winding and 330.0 ohms single winding

Duty Type:

Continuous

Mounting Facility Type And Quantity:

2 unthreaded hole single mounting facility

Storage Type:

General purpose warehouse

Mounting Facility Pattern:

In-line single mounting facility

Nonpile-up Main Contact Arrangement:

6 pole, double throw, one position momentary

Operating Voltage Rating And Type At Specificationified Temp:

26.5 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

300.0 milliamperes ac resistive load and 1.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Test Data Document:

81349-mil-r-5757 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

20 pin all functions

NSN 5945-00-458-7204

Electromagnetic Relay - Page 2 of 2



Spec	ifica	ation	Data:
------	-------	-------	-------

81349-mil-r-5757/1 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300