# NSN 5945-00-463-2705

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-463-2705

view Online at https://acrobasegroup.com/nsi//0340-00-400-2700
Thread Class:
2b single mounting facility
Thread Direction:
Right-hand single mounting facility
Overall Length:
2.850 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.750 inches single mounting facility
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.200 inches single mounting facility
Overall Height:
0.875 inches
Overall Width:
1.952 inches
Case Material:
Metal
Environmental Protection:
Hermetic
Fragility Factor:
Moderately rugged
Frequency In Hertz:
400.0
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
4 threaded hole single mounting facility
Storage Type:
General purpose warehouse
Cubic Measure:
4.687 cubic inches
Thready Qty Per Inch (tpi):
40 single mounting facility

Thread Size:

0.112 inches single mounting facility

# NSN 5945-00-463-2705

Electromagnetic Relay - Page 2 of 2



Mounting	<b>Facility</b>	Pattern:

Rectangular single mounting facility

### **Nonpile-up Main Contact Arrangement:**

2 pole, double throw, one position momentary

Time Delay:

0.02 seconds fixed operate time

### **Operating Voltage Rating And Type At Specificationified Temp:**

115.0 volts ac 25 degrees celsius single winding

### Main Contact Load Current Rating At Maximum Rated Voltage:

300.0 milliamperes ac resistive load and 10.0 amperes dc resistive load

### **Main Contact Maximum Voltage Rating In Volts:**

115.0 ac and 24.0 dc

#### **Thread Series Designator:**

Unc single mounting facility

#### **Terminal Type And Quantity:**

8 wire hook all functions

Shelf Life:

N/a

**Unit Of Measure:** 

**Demilitarization:** 

No

Fiig:

A03300