## NSN 5945-00-465-4379

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-465-4379				
Thread Class:				
2a single mounting facility				
Overall Length:				
1.490 inches				
Center To Center Distance Between Mounting Facilities Parallel To Length:				
0.800 inches single mounting facility				
Center To Center Distance Between Mounting Facilities Parallel To Width:				
0.220 inches single mounting facility				
Overall Height:				
0.810 inches				
Overall Width:				
0.810 inches				
Environmental Protection:				
Hermetic				
Fragility Factor:				
Moderately rugged				
Winding Quantity:				
1				
Purpose For Which Designed:				
General				
Coil Quantity:				
1				
Winding Dc Resistance Rating:				
900.0 ohms single winding and 1.1 kilohms single winding				
Duty Type:				
Continuous				
Mounting Facility Type And Quantity:				
2 threaded stud single mounting facility				
Storage Type:				
General purpose warehouse				
Features Provided:				
Polarized				
Thread Size:				
0.112 inches single mounting facility				
Mounting Facility Pattern:				
Diagonal single mounting facility				
Nonpile-up Main Contact Arrangement:				
2 pole, double throw, one position momentary				
Operating Current Rating And Type:				

10.0 milliamperes dc single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

300.0 milliamperes ac resistive load and 750.0 milliamperes dc resistive load

## NSN 5945-00-465-4379

Electromagnetic Relay - Page 2 of 2



Main Contact Maximum	Voltage	Rating	ın v	volts:
115 0 ac and 29 0 da				

115.0 ac and 28.0 dc

**Thread Series Designator:** 

Unc single mounting facility

**Terminal Type And Quantity:** 

8 pin all functions

Shelf Life:

**Unit Of Measure:** 

N/a

Demilitarization:

No

Fiig:

A03300