NSN 5945-00-465-8171

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-465-8171
Overall Length:
1.453 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.067 inches single mounting facility
Center To Center Distance Between Mounting Facilities Parallel To Width:
0.130 inches single mounting facility
Overall Height:
1.491 inches
Overall Width:
0.400 inches
Mounting Slot Width:
0.110 inches single mounting facility
Case Material:
Metal
Environmental Protection:
Hermetic
Fragility Factor:
Moderately rugged
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Winding Dc Resistance Rating:
90.0 ohms single winding and 110.0 ohms single winding
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
2 slotted hole single mounting facility
Storage Type:
General purpose warehouse
Cubic Measure:
0.866 cubic inches
Mounting Facility Pattern:
Diagonal single mounting facility
Nonpile-up Main Contact Arrangement:
2 pole, double throw, one position momentary
Operating Current Rating And Type:

40.0 milliamperes dc single winding

NSN 5945-00-465-8171

Electromagnetic Relay - Page 2 of 2



Time I	Delay:
--------	--------

0.015 seconds fixed operate time

Main Contact Load Current Rating At Maximum Rated Voltage:

100.0 milliamperes dc lamp load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Test Data Document:

81349-mil-r-5757 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

8 wire hook all functions

Specification Data:

81349-mil-r-5757/13 government specification

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A03300