NSN 5945-00-466-3413

Electromagnetic Relay - Page 1 of 2

81349-mil-r-5757/38 government specification



View Online at https://aerobasegroup.com/nsn/5945-00-466-3413

Overall Length:
0.280 inches
Overall Diameter:
0.370 inches
Case Material:
Metal
Environmental Protection:
Hermetic
Fragility Factor:
Moderately rugged
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Winding Dc Resistance Rating:
1.2 kilohms single winding and 1.5 kilohms single winding
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
1 plug-in terminal single mounting facility
Storage Type:
General purpose warehouse
Nonpile-up Main Contact Arrangement:
1 pole, double throw, one position momentary
Time Delay:
0.002 seconds fixed operate and release time
Operating Voltage Rating And Type At Specificationified Temp:
6.0 volts dc 25 degrees celsius single winding
Main Contact Load Current Rating At Maximum Rated Voltage:
100.0 milliamperes dc lamp load
Main Contact Maximum Voltage Rating In Volts:
28.0 dc
Test Data Document:
81349-mil-r-5757 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
5 pin all functions
Specification Data:

NSN 5945-00-466-3413

Electromagnetic Relay - Page 2 of 2



_					
•	n	0 1	•	12	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300