

View Online at <https://aerobasegroup.com/nsn/5945-00-467-1684>

Overall Length:

3.906 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.250 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.687 inches single mounting facility

Overall Height:

2.976 inches

Overall Width:

3.718 inches

Environmental Protection:

Dustproof

Unthreaded Mounting Hole Diameter:

0.218 inches single mounting facility

Winding Quantity:

1

Coil Quantity:

1

Duty Type:

Continuous

Mounting Facility Type And Quantity:

4 unthreaded hole single mounting facility

Mounting Facility Pattern:

Rectangular single mounting facility

Nonpile-up Main Contact Arrangement:

3 pole, single throw, normally open, momentary action

Operating Current Rating And Type:

500.0 milliamperes dc single winding

Nonpile-up Auxiliary Contact Arrangement:

1 pole, single throw, normally open, momentary action and 1 pole, double throw, two positions momentary

Auxiliary Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Operating Voltage Rating And Type At Specificationified Temp:

28.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

75.0 amperes ac resistive load and 75.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Test Data Document:

81349-mil-r-6106 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

12 pin all functions

Specification Data:

96906-ms27714 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300

Mil-std (military Standard):

Mil-r-6106 spec.